



GENERAL NOTES:

- 1) HR UNITS ARE AVAILABLE IN STANDARD WIDTHS (MIN. HR48 WITH 52" O.D. OF CURB) (CUSTOM SIZES ARE AVAILABLE)
- 2) RAFTER SPACING TO BE 4'-0" MAX.
- 3) ALL DOME UNITS MEET OR EXCEED AAMA RECOMMENDATIONS.
- 4) STRUCTURAL RIBS ARE REQUIRED ON HR MODEL -120 THRU -192.
- 5) HEAVY DUTY STRUCTURAL RIBS ARE REQUIRED ON HR MODEL -204 AND UP.
- 6) CENTER PURLINS ARE REQUIRED ON HR MODEL -72 AND UP.
- 7) 45° PURLINS ARE REQUIRED ON HR MODEL 132 AND UP.
- 8) VERTICAL MULLION REQUIRED ON HR MODEL -72 AND UP.
- 9) VERTICAL ENDS WILL BE SHIPPED ASSEMBLED. REMAINDER OF UNIT TO BE SHIPPED KNOCKED DOWN.
- 10) (DD) DENOTES DOUBLE DOME.

MODEL	DIM "A"
HR-48	52"
HR-60	64"
HR-72	76"
HR-84	88"
HR-96	100"
HR-108	112"
HR-120	124"
HR-132	136"
HR-144	148"
HR-156	160"
HR-168	172"
HR-180	184"
HR-192	196"
HR-204	208"
HR-216	220"
HR-228	232"
HR-240	244"

