



MODEL	DIM "A"	UNIT RISE
BVV-36	39"	10.2"
BVV-42	45"	11.7"
BVV-46	49"	12.7"
BVV-48	51"	13.2"
BVV-54	57"	14.7"
BVV-60	63"	16.2"
BVV-72	75"	19.2"
BVV-84	87"	22.2"
BVV-96	99"	25.2"
BVV-102	105"	26.7"
BVV-120	123"	31.2"
BVV-144	147"	37.3"

GENERAL NOTES:

- 1) BVV UNITS ARE AVAILABLE IN STANDARD WIDTHS.
(CUSTOM SIZES ARE AVAILABLE)
- 2) RAFTER SPACING TO BE 4'-0" MAX.
- 3) ALL UNITS MEET OR EXCEED AAMA RECOMMENDATIONS.
- 4) VERTICAL MULLION REQUIRED FOR BVV MODEL -72 THRU MODEL -144.
- 5) STRUCTURAL RIBS ARE REQUIRED ON BVV MODEL -120 THRU 192" WIDE.
- 6) MODEL BVV-36 THRU BVV-54 UNITS UP TO 16'-0" CAN BE SHIPPED ASSEMBLED.
- 7) MODEL BVV-60 THRU BVV-96 UNITS UP TO 12'-0" CAN BE SHIPPED ASSEMBLED.
- 8) UNITS LONGER THAN 16'-0" WILL BE SHIPPED KNOCKED WITH ENDS ASSEMBLED.
- 8) ALL BARREL VAULTS WITH ANODIZED FRAMES WILL BE SHIPPED KNOCKED DOWN DUE TO ANODIZING TANK SIZE LIMITATIONS.
- 9) (DD) DENOTES DOUBLE DOME.

