



MODEL	R.O. OF CURB	OUTER DOME RISE	INNER DOME RISE
C-30	24"	8"	6"
C-36	31"	11"	9"
C-48	43"	13"	11"
C-60	54"	19"	15"
C-72	67"	22"	18"
C-84	79"	25"	21"
C-96	91"	29"	25"

GENERAL NOTES:

- 1) DDC UNITS ARE AVAILABLE IN STANDARD SIZES (CUSTOM SIZES ARE AVAILABLE)
- 2) ALL DOME UNITS MEET OR EXCEED AAMA RECOMENDATIONS

- OUTER DOME
- INNER DOME
- BUTYL TAPE
- ALUMINUM RETAINER
- DRYSEAL GASKET
- #10x<sup>3</sup>/<sub>4</sub>" ALUM. TEK SCREWS @ 6" O.C.

**IMPORTANT !!!**

THIS AREA MUST BE KEPT CLEAR OF ALL FLASHINGS, SEALANTS & ROOFING MATERIALS SO SKYLIGHT WILL WEEP PROPERLY (TYPICAL ALL SIDES)

1/2"

- CORK GASKET
- FABRICATED ALUM. CURB
- LAP SEALANT BY OTHERS
- ALUM. OUTER BODY
- 1" FIBERGLASS INSULATION (INDUSTRY STANDARD)
- ALUM. INNER BODY
- ROOFING MEMBRANE AND BONDING ADHESIVE (BY OTHERS)

CURB HEIGHT

STANDARD CURB HEIGHT AVAILABLE IN 4" OR 9". CUSTOM 12" ALSO AVAILABL

CORROSION RESISTANT NAILS AT 6" O.C. (BY INSTALLER)

S.S. FASTENERS WILL BE REQUIRED IF PENETRATING PRESSURE TREATED WOOD

4"

ROUGH OPENING DIAMETER OF CURB

