



MODEL	DIM "A"
QR-24	26 7/8"
QR-30	32 7/8"
QR-36	38 7/8"
QR-42	44 7/8"
QR-48	50 7/8"
QR-54	56 7/8"
QR-60	62 7/8"
QR-72	74 7/8"
QR-84	86 7/8"
QR-96	98 7/8"
QR-108	110 7/8"
QR-120	122 7/8"
QR-132	134 7/8"
QR-144	146 7/8"
QR-156	158 7/8"
QR-168	170 7/8"

GENERAL NOTES:

- 1) QR UNITS ARE AVAILABLE IN STANDARD WIDTHS (MIN QR24 WITH 26 7/8" O.D. OF CURB) (CUSTOM SIZES ARE AVAILABLE)
- 2) RAFTER SPACING TO BE 4'-0" MAX.
- 3) ALL DOME UNITS MEET OR EXCEED AAMA RECOMMENDATIONS.
- 4) STRUCTURAL RIBS ARE REQUIRED ON QR MODEL -72 THRU -96.
- 5) HEAVY DUTY STRUCTURAL RIBS ARE REQUIRED ON QR MODEL -108 AND UP.
- 6) 45° PURLINS ARE REQUIRED ON QR MODEL -72 AND UP.
- 7) VERTICAL ENDS WILL BE SHIPPED ASSEMBLED. REMAINDER OF UNIT TO BE SHIPPED KNOCKED DOWN.
- 8) (DD) DENOTES DOUBLE DOME.





